Summary of the Hall D Spring 2019 run

A. Deur Jefferson Lab



A. Deur. GlueX collaboration meeting. 05/14/2019

Summary of the Hall D Spring 2019 run

A. Deur Jefferson Lab

Spring 2019 run plan: https://halldweb.jlab.org/wiki/index.php/Run_Coordination_Meetings:Spring2019_Run Spring 2019 run coordinator summaries: https://https://https://https://halldweb.jlab.org/hdops/wiki/index.php/Run_Coordination_Meetings:Spring2019_Run All the run summaries: <a href="https://https//https://https://https://https://https/https//https//https//https//https//https//https



A. Deur. GlueX collaboration meeting. 05/14/2019

Initial schedule:

- 1. Jan. 22nd Feb 7th: Electron beam restoration;
- 2. Feb. 7th Feb. 20th: DIRC Commissioning; (part 1: first optical box);
- **3**. Feb. 20th: Charge Pion Polarizability (CPP) test;
- 4. Feb. 20th morning Apr. 15th: PrimEx-η run, part 1.



Initial schedule:

- 1. Jan. 22nd Feb 7th: Electron beam restoration;
- 2. Feb. 7th Feb. 20th: DIRC Commissioning; (part 1: first optical box); DIRC commissioning page: <u>https://halldweb.jlab.org/wiki/index.php/Spring_2019_DIRC_Commissioning</u>
- **3.** Feb. 20th: Charge Pion Polarizability (CPP) test; https://halldweb.jlab.org/wiki/index.php/CPP_Beam_Test_Feb._2019 CCP test pages: https://www.overleaf.com/read/yzzgqtddbfmy
- 4. Feb. 20th morning Apr. 15th: PrimEx-η run, part 1. PrimEx runplan page: <u>https://halldweb.jlab.org/wiki/index.php/Spring_2019_Primex</u>



Initial schedule:

- 1. Jan. 22nd Feb 7th: Electron beam restoration;
- 2. Feb. 7th Feb. 20th: DIRC Commissioning; (part 1: first optical box);
- **3.** Feb. 20th: Charge Pion Polarizability (CPP) test;
- 4. Feb. 20th morning Apr. 15th: PrimEx-η run, part 1.

Leadership: C. Meyer/M. Shepherd, E. Chudakov/E. Smith

Run Coordinators:

Feb. 7th-Feb. 13th Alexandre Deur (accelerator restoration) Feb. 7th-Feb. 13th, 7 days: Alexandre Deur Feb. 13th-Feb. 20th, 7 days: Wenliang Li https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w4 Feb. 20th-Feb. 27th, 7 days: Sean Dobbs https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w5 Feb. 27th-March 6th, 7 days: Justin Stevens https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w6 March 6th-March 13th, 7 days: Alexander Austregesilo https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w7 March 13th-March 20th, 7 days: Colin Gleason https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w8 March 20th-March 27th, 7 days: Richard Jones https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w9 March 27th-Apr. 3rd, 7 days: Stuart Fegan https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w10 Apr. 3rd-Apr. 10th, 7 days: Ilya Larin https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w12 Apr. 10th-Apr. 15th, 5 days: Joshua Crafts https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w11



Initial schedule:

- 1. Jan. 22nd Feb 7th: Electron beam restoration;
- 2. Feb. 7th Feb. 20th: DIRC Commissioning; (part 1: first optical box);
- **3.** Feb. 20th: Charge Pion Polarizability (CPP) test;
- 4. Feb. 20th morning Apr. 15th: PrimEx-η run, part 1.

Leadership: C. Meyer/M. Shepherd, E. Chudakov/E. Smith

Run Coordinators:

Feb. 7th-Feb. 13th Alexandre Deur (accelerator restoration) Feb. 7th-Feb. 13th, 7 days: Alexandre Deur Feb. 13th-Feb. 20th, 7 days: Wenliang Li https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w4 Feb. 20th-Feb. 27th, 7 days: Sean Dobbs https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w5 Feb. 27th-March 6th, 7 days: Justin Stevens https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w6 March 6th-March 13th, 7 days: Alexander Austregesilo https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w7 March 13th-March 20th, 7 days: Colin Gleason https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w8 March 20th-March 27th, 7 days: Richard Jones https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w9 March 27th-Apr. 3rd, 7 days: Stuart Fegan https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w10 Apr. 3rd-Apr. 10th, 7 days: Ilya Larin https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w12 Apr. 10th-Apr. 15th, 5 days: Joshua Crafts https://halldweb.jlab.org/wiki/index.php/Run_Coordinator_report:_spring_2019_w11

Physics Division Liaison: Lubomir Penchev.

Analysis Coordinator: Alexander Austregesilo.

Run coordination, subsystem status, data quality monitoring, offline analysis are discussed at daily RC meetings (8:45am, counting house).



Initial schedule:

- 1. Jan. 22nd Feb 7th: Electron beam restoration;
- 2. Feb. 7th Feb. 20th: DIRC Commissioning; (part 1: first optical box);
- **3**. Feb. 20th: Charge Pion Polarizability (CPP) test;
- 4. Feb. 20th morning Apr. 15th: PrimEx-η run, part 1.



Actual schedule: 9th

- Jan. 22nd Feb 7th: Electron beam restoration;
 9th
 Feb. 7th Feb. 20th: DIRC Commissioning; (part 1: first optical box);
- **3**. Feb. 20th: Charge Pion Polarizability (CPP) test;
- 4. Feb. 20th morning Apr. 15th: PrimEx-η run, part 1.



Actual schedule: 9th

1. Jan. 22nd - Feb 7th: Electron beam restoration;

2. Feb. 7th - Feb. 20th: DIRC Commissioning; (part 1: first optical box);

3. Feb. 20th: Charge Pion Polarizability (CPP) test;

4. Feb. 20th morning - Apr. 15th: PrimEx-η run, part 1.

Fall 2018 run 1. Aug. 21st - Oct. 28th: GlueX-1 final run (11.6 GeV) 2. Oct. 28th - Nov 19th: DIRC and ComCal installations (accelerator still at 11.6 GeV until 11/16 3. Nov 20th - Dec. 12th: GlueX-II (DIRC) and PrimEx (ComCal) tests. E=10.3 GeV 4. Dec. 13th - Dec. 19th: GlueX-II and PrimEx tests. E=9.0 GeV	6/2018) Also, take GlueX-I data at lower energy, to compare with CLAS	Fall 2018 run Actual events: Beam available for physics on Sept. 21st Duc to late statt: ran Gluex production until Nov. 24th 1. Aug. 21st - Oct. 28th: GlueX-I final run (11.6 GeV) 2. Oct. 28th - Nov 19th: DIRC and ComCal installations (accelerator still at 11.6 GeV until 11/1/2018) 3. Nov 20th - Dec. 12th: GlueX-II (DIRC) and PrimEx (ComCal) tests. E=10.3 GeV 24th 4. Dec. 13th - Dec. 19th: GlueX-II and PrimEx tests. E=9.0 GeV DIRC not ready for installation Direc not ready for installation Most glue beam down time (beam study, spin dance, etc.)
Jefferson Lab Thomas Jefferson National Accelerator Facility A. Deur. GlueX colla Exploring the Nature of Matter A. Deur. GlueX colla	aboration meeting. 02/21/2019	A. Deur: GlueX collaboration meeting, 02/21/2019



Spring 2019 run configuration

•Energy: 11.61 GeV until March 5th then 11.17 GeV (Fall 16-Spring 18: 11.64 GeV. Energy was lowered to 11.17 due to high RF trip rate and end of critical high-energy requirement by Hall C program.)

•4-hall ops, 1-pass for Hall A, 5-pass for Hall B, 3-5 pass for Hall C. D: 5.5-pass. High currents for A & C.



Spring 2019 run configuration

•Energy: 11.61 GeV until March 5th then 11.17 GeV (Fall 16-Spring 18: 11.64 GeV. Energy was lowered to 11.17 due to high RF trip rate and end of critical high-energy requirement by Hall C program.)

•4-hall ops, 1-pass for Hall A, 5-pass for Hall B, 3-5 pass for Hall C. D: 5.5-pass. High currents for A & C.

•Hall D configuration:

•Solenoid at 1350A (DIRC commissioning) or ramped-down (PrimEx-eta run).

•Rep. rate 250 MHz.

•Slit shared with C (as in Fall 18. It was with B in Fall 17 and A in Spring 18)

•Beam current 1 nA-1.5 μ A. $\frac{225 \text{ nA}}{200 \text{ nA}}$ for most of DIRC commissioning. Up to 900 nA for high intensity tests.

•Radiators: DIRC comm.: old (degraded) 17 μm J70-104 diamond. Then PrimEx: 10 μm Al. radiator;
•5mm collimator hole;

•LH₂ target (DIRC comm.), then PrimEx: no target, solid Be foil target, then empty and filled L⁴He target interspersed.

•TPol on during DIRC runs for systematic studies, with 75 μ m TPol convertor. Off during PrimEx, with 750 μ m TPol convertor for the PS.

•CDC & FDC: on for DIRC comm. Off at start of PrimEx. Then CDC on (March 8th) to provide vertex monitoring and background diagnostic for little DAQ performance cost. FDC off except for short time during low lumi. runs.



Spring 2019 run configuration

•Energy: 11.61 GeV until March 5th then 11.17 GeV (Fall 16-Spring 18: 11.64 GeV. Energy was lowered to 11.17 due to high RF trip rate and end of critical high-energy requirement by Hall C program.)

•4-hall ops, 1-pass for Hall A, 5-pass for Hall B, 3-5 pass for Hall C. D: 5.5-pass. High currents for A & C.

•Hall D configuration:

•Solenoid at 1350A (DIRC commissioning) or ramped-down (PrimEx-eta run).

•Rep. rate 250 MHz.

•Slit shared with C (as in Fall 18. It was with B in Fall 17 and A in Spring 18)

•Beam current 1 nA-1.5 μ A. $\frac{225 \text{ nA}}{200 \text{ nA}}$ for most of DIRC commissioning. Up to 900 nA for high intensity tests. 200 nA for standard PrimEx production.

•Radiators: DIRC comm.: old (degraded) 17 µm J70-104 diamond. Then PrimEx: 10 µm Al. radiator;

•5mm collimator hole;

•LH₂ target (DIRC comm.), then PrimEx: no target, solid Be foil target, then empty and filled L⁴He target interspersed.

•TPol on during DIRC runs for systematic studies, with 75 μ m TPol convertor. Off during PrimEx, with 750 μ m TPol convertor for the PS.

•CDC & FDC: on for DIRC comm. Off at start of PrimEx. Then CDC on (March 8th) to provide vertex monitoring and background diagnostic for little DAQ performance cost. FDC off except for short time during low lumi. runs.

Hall D goals:

- •Commission DIRC's first optical box;
- •DAQ and Trigger high-intensity tests during DIRC commissioning;
- •CPP tests during last day of DIRC commissioning;
- •PrimEx production on Be and ⁴He targets;
- •TAC runs during PrimEx run;
- •(TRD non-invasive runs).



- 1. Verify electron beam quality and establish photon beam.
- 2. Detector and beamline checkout.
- 3. Check 17 µm diamond (JD70-104) alignement.



- 1. Verify electron beam quality and establish photon beam.
- 2. Detector and beamline checkout.
- 3. Check 17 µm diamond (JD70-104) alignement.
- 4. DIRC commissioning
 - Standard configuration: 17 μm diamond, 225 nA, 5 mm hole, TPol on (for syst. studies. Not necessary for DIRC) 75 μm TPol convertor. Solenoid at 1350 A.
 - 2. Luminosity scans on amorphous radiator. 50-900 nA on 10 μ m Al (1.12·10⁻⁴ R.L.)
 - 3. Harp scan: Only once in the middle of the DIRC commissioning (beside the ones done during beam set-up).
 - 4. One Empty target run.



- 1. Verify electron beam quality and establish photon beam.
- 2. Detector and beamline checkout.
- 3. Check 17 µm diamond (JD70-104) alignement.
- 4. DIRC commissioning
 - Standard configuration: 17 μm diamond, 225 nA, 5 mm hole, TPol on (for syst. studies. Not necessary for DIRC) 75 μm TPol convertor. Solenoid at 1350 A.
 - 2. Luminosity scans on amorphous radiator. 50-900 nA on 10 μ m Al (1.12·10-4 R.L.)
 - 3. Harp scan: Only once in the middle of the DIRC commissioning (beside the ones done during beam set-up).
 - 4. One Empty target run.
- 5. CPP (Charged pion polarizability) tests
 - 1. Move downstream platform downstream
 - 2. Install passive shielding in front of TOF.
 - 3. Set-up and check specific CPP trigger.
 - 4. Tests (to be done for various thicknesses of passive shielding).
 - 5. End of test: ramp down solenoid, remove shielding.



- 1. Verify electron beam quality and establish photon beam.
- 2. Detector and beamline checkout.
- 3. Check 17 µm diamond (JD70-104) alignement.
- 4. DIRC commissioning
 - Standard configuration: 17 μm diamond, 225 nA, 5 mm hole, TPol on (for syst. studies. Not necessary for DIRC) 75 μm TPol convertor. Solenoid at 1350 A.
 - 2. Luminosity scans on amorphous radiator. 50-900 nA on 10 μ m Al (1.12·10⁻⁴ R.L.)
 - 3. Harp scan: Only once in the middle of the DIRC commissioning (beside the ones done during beam set-up).
 - 4. One Empty target run.
- 5. CPP (Charged pion polarizability) tests
 - 1. Move downstream platform downstream
 - 2. Install passive shielding in front of TOF.
 - 3. Set-up and check specific CPP trigger.
 - 4. Tests (to be done for various thicknesses of passive shielding).
 - 5. End of test: ramp down solenoid, remove shielding.
- 6. PrimEx-η
 - Standard configuration: 10 μm Al (11.2·10⁻⁵ R.L). Beam current depends on target. 750 μm TPol convertor. Solenoid off.
 - 2. Snake scans for ComCal calibration.
 - 3. Production on no target, solid Be foil target, then ⁴He target (full and empty).
 - 4. Two TAC runs (to be done with the TAC detector, not with ComCal).
 - 5. HARP scan (only Hall D harp): 10 min. Every two days.
 - 6. Long mode 10 min runs to monitor neutron radiation damage to ST due to nuclear target higher neutron yield. Twice or Thrice a week.



- Verify electron beam quality and establish photon beam. Started 2 days late due to CEBAF cooling issues. Initially, feared a longer delay, but physics quality beam
- Detector and beamline checkout.
- 3.
- DIRC commissioning 4.
 - Was turned off during high luminosity runs. Standard configuration: 17 μm diamond, 225 nA, 5 mm hole, TPol on (for syst. studies. Not necessary for DIRC) 75 μm TPol convertor. Solenoid at 1350 A. But ramp up delayed due to motherboard demise. 1.
 - Luminosity scans on amorphous radiator. 50-900 nA on 10 µm Al (1.12·10⁻⁴ R.L.) 2.
 - Harp scan: Only once in the middle of the DIRC commissioning (beside the ones done during beam set-up). 3.
 - One Empty target run. 4.
- CPP (Charged pion polarizability) tests 5.
 - Move downstream platform downstream
 - Install passive shielding in front of TOF. 2.
 - Set-up and check specific CPP trigger. 3.
 - Tests (to be done for various thicknesses of passive shielding). 4.
 - End of test: ramp down solenoid, remove shielding. 5.
- PrimEx-ŋ 6.
 - Standard configuration: 10 µm Al (11.2·10⁻⁵ R.L). Beam current depends on target. 750 µm TPol convertor. 1. Solenoid off.
 - Snake scans for ComCal calibration. 2.
 - Production on no target, solid Be foil target, then ⁴He target (full and empty). 3.
 - Two TAC runs (to be done with the TAC detector, not with ComCal). 4.
 - 5. HARP scan (only Hall D harp): 10 min. Every two days.
 - Long mode 10 min runs to monitor neutron radiation damage to ST due to nuclear target higher neutron yield. 6. Twice or Thrice a week.



("commissioning quality" for Hall D) was very quickly established.

Check 17 µm diamond (JD70-104) alignement. ✓ Not the greatest coherent peak ever seen (used-up diamond good enough for commissioning).

> Done more than once (thrice), due to concern after long beam down time.

- Verify electron beam quality and establish photon beam. Started 2 days late due to CEBAF cooling issues. Initially, feared a longer delay, but physics quality beam
- Detector and beamline checkout.
- 3.
- DIRC commissioning 4.
 - Was turned off during high luminosity runs. Standard configuration: 17 µm diamond, 225 nA, 5 mm hole, TPol on (for syst. studies. Not necessary for DIRC) 75 µm TPol convertor. Solenoid at 1350 A. But ramp up delayed due to motherboard demise. 1.
 - Luminosity scans on amorphous radiator. 50-900 nA on 10 µm Al (1.12·10⁻⁴ R.L.) 2.
 - Harp scan: Only once in the middle of the DIRC commissioning (beside the ones done during beam set-up). 3. Done more than once (thrice), due to concern after
 - One Empty target run. 4.

CPP (Charged pion polarizability) tests 5.

Not at nominal position.

- Move downstream platform downstream Install passive shielding in front of TOF, 2.
- Set-up and check specific CPP trigger. 3.
- Tests (to be done for various thicknesses of passive shielding). 4.
- End of test: ramp down solenoid, remove shielding. 5.
- PrimEx-ŋ 6.
 - Standard configuration: 10 µm Al (11.2·10⁻⁵ R.L). Beam current depends on target. 750 µm TPol convertor. 1. Solenoid off.
 - Snake scans for ComCal calibration. 2.
 - Production on no target, solid Be foil target, then ⁴He target (full and empty). 3.
 - Two TAC runs (to be done with the TAC detector, not with ComCal). 4.
 - 5. HARP scan (only Hall D harp): 10 min. Every two days.
 - Long mode 10 min runs to monitor neutron radiation damage to ST due to nuclear target higher neutron yield. 6. Twice or Thrice a week.



("commissioning quality" for Hall D) was very quickly established.

Check 17 µm diamond (JD70-104) alignement. ✓ Not the greatest coherent peak ever seen (used-up diamond good enough for commissioning).

long beam down time.

- Verify electron beam quality and establish photon beam. Started 2 days late due to CEBAF cooling issues. Initially, feared a longer delay, but physics quality beam
- Detector and beamline checkout.
- Check 17 µm diamond (JD70-104) alignement. 3.
- DIRC commissioning 4.
 - Was turned off during high luminosity runs. Standard configuration: 17 µm diamond, 225 nA, 5 mm hole, TPol on (for syst. studies. Not necessary for DIRC) 75 µm TPol convertor. Solenoid at 1350 A. But ramp up delayed due to motherboard demise. 1.
 - Luminosity scans on amorphous radiator. 50-900 nA on 10 µm Al (1.12·10⁻⁴ R.L.) 2.
 - Harp scan: Only once in the middle of the DIRC commissioning (beside the ones done during beam set-up). 3. Done more than once (thrice), due to concern after
 - One Empty target run. 4.
- CPP (Charged pion polarizability) tests 5. Move downstream platform downstream

Not at nominal position.

- Set-up and check specific CPP trigger. ✓ 3.
 - Tests (to be done for various thicknesses of passive shielding). 4.
 - End of test: ramp down solenoid, remove shielding. 5.

Install passive shielding in front of TOF,

PrimEx-ŋ 6.

2.

- Standard configuration: 10 um Al (11.2 \cdot 10⁻⁵ R.L). Beam current depends on target. 750 µm TPol convertor. Solenoid off. Solenoid warmed up on March 26th 1.
 - Snake scans for ComCal calibration. Done at the start and end of Spring run period.
- 2. Production on no target, solid Be foil target, then ⁴He target (full and empty). 3.
- Two TAC runs (to be done with the TAC detector, not with ComCal). Only one done w/ TAC, + one done w/ ComCal HARP scan (only Hall D harp): 10 min. Every two days. Not done every two days. Only after long beam down times. 4.
- 5.
- Long mode 10 min runs to monitor neutron radiation damage to ST due to nuclear target higher neutron yield. \checkmark 6. Twice or Thrice a week.



("commissioning quality" for Hall D) was very quickly established.

✓ Not the greatest coherent peak ever seen (used-up diamond good enough for commissioning).

long beam down time.

• Solenoid power supply motherboard failed. Delayed the solenoid ramp up. Did not cost us time (thanks to accelerator ops who used the time to tune the beam to other halls). <u>https://logbooks.ilab.org/entry/3649136</u>

- Solenoid power supply motherboard failed. Delayed the solenoid ramp up. Did not cost us time (thanks to accelerator ops who used the time to tune the beam to other halls). <u>https://logbooks.jlab.org/entry/3649136</u>
- DIRC SSP firmware. Caused DAQ rates to drop to 0. Problem promptly patched after intense work by A. Somov and Ben Raydo. <u>https://logbooks.jlab.org/entry/3652894</u>

- Solenoid power supply motherboard failed. Delayed the solenoid ramp up. Did not cost us time (thanks to accelerator ops who used the time to tune the beam to other halls). <u>https://logbooks.jlab.org/entry/3649136</u>
- DIRC SSP firmware. Caused DAQ rates to drop to 0. Problem promptly patched after intense work by A. Somov and Ben Raydo. <u>https://logbooks.jlab.org/entry/3652894</u>
- TOF RF signal initially reported uncorrelated times. Problem found and fixed by Beni: Main input cable was unplugged with wrong signals coming from an active unlocked phase lock circuit.

- Solenoid power supply motherboard failed. Delayed the solenoid ramp up. Did not cost us time (thanks to accelerator ops who used the time to tune the beam to other halls). <u>https://logbooks.jlab.org/entry/3649136</u>
- DIRC SSP firmware. Caused DAQ rates to drop to 0. Problem promptly patched after intense work by A. Somov and Ben Raydo. <u>https://logbooks.jlab.org/entry/3652894</u>
- TOF RF signal initially reported uncorrelated times. Problem found and fixed by Beni: Main input cable was unplugged with wrong signals coming from an active unlocked phase lock circuit.
- Energy lowered by ~450 MeV due to unsustainable RF-trips (March 5th). Also, the Hall C program requiring highest energy had ended. Lower f.o.m for PrimEx. <u>https://logbooks.jlab.org/entry/3679070</u>
- Short term beam energy drift of up to 10 MeV (CEBAF path length changes, or no energy lock when Hall C was down: Hall A at 1-pass). Overall energy drift during 11.2 GeV period was small (5 MeV). Compare with 12 MeV in Fall 2018. https://logbooks.jlab.org/entry/3679070

- Solenoid power supply motherboard failed. Delayed the solenoid ramp up. Did not cost us time (thanks to accelerator ops who used the time to tune the beam to other halls). <u>https://logbooks.jlab.org/entry/3649136</u>
- DIRC SSP firmware. Caused DAQ rates to drop to 0. Problem promptly patched after intense work by A. Somov and Ben Raydo. <u>https://logbooks.jlab.org/entry/3652894</u>
- TOF RF signal initially reported uncorrelated times. Problem found and fixed by Beni: Main input cable was unplugged with wrong signals coming from an active unlocked phase lock circuit.
- Energy lowered by ~450 MeV due to unsustainable RF-trips (March 5th). Also, the Hall C program requiring highest energy had ended. Lower f.o.m for PrimEx. <u>https://logbooks.jlab.org/entry/3679070</u>
- Short term beam energy drift of up to 10 MeV (CEBAF path length changes, or no energy lock when Hall C was down: Hall A at 1-pass). Overall energy drift during 11.2 GeV period was small (5 MeV). Compare with 12 MeV in Fall 2018. https://logbooks.jlab.org/entry/3679070
- Rapid transmission degradation (days). Not a critical issue with unpolarized beam, but need to be better understood. <u>https://logbooks.jlab.org/entry/3675433</u>
- PS/Main trigger rate time dependence (Not critical for PrimEx thanks to Compton rate normalization) https://logbooks.jlab.org/entry/3675433

- Solenoid power supply motherboard failed. Delayed the solenoid ramp up. Did not cost us time (thanks to accelerator ops who used the time to tune the beam to other halls). <u>https://logbooks.jlab.org/entry/3649136</u>
- DIRC SSP firmware. Caused DAQ rates to drop to 0. Problem promptly patched after intense work by A. Somov and Ben Raydo. <u>https://logbooks.jlab.org/entry/3652894</u>
- TOF RF signal initially reported uncorrelated times. Problem found and fixed by Beni: Main input cable was unplugged with wrong signals coming from an active unlocked phase lock circuit.
- Energy lowered by ~450 MeV due to unsustainable RF-trips (March 5th). Also, the Hall C program requiring highest energy had ended. Lower f.o.m for PrimEx. <u>https://logbooks.jlab.org/entry/3679070</u>
- Short term beam energy drift of up to 10 MeV (CEBAF path length changes, or no energy lock when Hall C was down: Hall A at 1-pass). Overall energy drift during 11.2 GeV period was small (5 MeV). Compare with 12 MeV in Fall 2018. https://logbooks.jlab.org/entry/3679070
- Rapid transmission degradation (days). Not a critical issue with unpolarized beam, but need to be better understood. <u>https://logbooks.jlab.org/entry/3675433</u>
- PS/Main trigger rate time dependence (Not critical for PrimEx thanks to Compton rate normalization) https://logbooks.jlab.org/entry/3675433

Will be discussed in beamline talk

- Solenoid power supply motherboard failed. Delayed the solenoid ramp up. Did not cost us time (thanks to accelerator ops who used the time to tune the beam to other halls). <u>https://logbooks.jlab.org/entry/3649136</u>
- DIRC SSP firmware. Caused DAQ rates to drop to 0. Problem promptly patched after intense work by A. Somov and Ben Raydo. <u>https://logbooks.jlab.org/entry/3652894</u>
- TOF RF signal initially reported uncorrelated times. Problem found and fixed by Beni: Main input cable was unplugged with wrong signals coming from an active unlocked phase lock circuit.
- Energy lowered by ~450 MeV due to unsustainable RF-trips (March 5th). Also, the Hall C program requiring highest energy had ended. Lower f.o.m for PrimEx. <u>https://logbooks.jlab.org/entry/3679070</u>
- Short term beam energy drift of up to 10 MeV (CEBAF path length changes, or no energy lock when Hall C was down: Hall A at 1-pass). Overall energy drift during 11.2 GeV period was small (5 MeV). Compare with 12 MeV in Fall 2018. https://logbooks.jlab.org/entry/3679070
- Rapid transmission degradation (days). Not a critical issue with unpolarized beam, but need to be better understood. <u>https://logbooks.jlab.org/entry/3675433</u>
- PS/Main trigger rate time dependence (Not critical for PrimEx thanks to Compton rate normalization) https://logbooks.jlab.org/entry/3675433
- Active collimator signal decay. (Still under investigation. Unclear impact, if any.)

- Solenoid power supply motherboard failed. Delayed the solenoid ramp up. Did not cost us time (thanks to accelerator ops who used the time to tune the beam to other halls). <u>https://logbooks.jlab.org/entry/3649136</u>
- DIRC SSP firmware. Caused DAQ rates to drop to 0. Problem promptly patched after intense work by A. Somov and Ben Raydo. <u>https://logbooks.jlab.org/entry/3652894</u>
- TOF RF signal initially reported uncorrelated times. Problem found and fixed by Beni: Main input cable was unplugged with wrong signals coming from an active unlocked phase lock circuit.
- Energy lowered by ~450 MeV due to unsustainable RF-trips (March 5th). Also, the Hall C program requiring highest energy had ended. Lower f.o.m for PrimEx. <u>https://logbooks.jlab.org/entry/3679070</u>
- Short term beam energy drift of up to 10 MeV (CEBAF path length changes, or no energy lock when Hall C was down: Hall A at 1-pass). Overall energy drift during 11.2 GeV period was small (5 MeV). Compare with 12 MeV in Fall 2018. https://logbooks.jlab.org/entry/3679070
- Rapid transmission degradation (days). Not a critical issue with unpolarized beam, but need to be better understood. <u>https://logbooks.jlab.org/entry/3675433</u>
- PS/Main trigger rate time dependence (Not critical for PrimEx thanks to Compton rate normalization) https://logbooks.jlab.org/entry/3675433
- Active collimator signal decay. (Still under investigation. Unclear impact, if any.)

https://logbooks.jlab.org/entry/3675240

• MCC lost control of Active Collimator. No alarm. Access needed to reboot IOC in Hall D. Need to have alarm and reset buttons in the counting room. https://logbooks.jlab.org/entry/3654003

- Solenoid power supply motherboard failed. Delayed the solenoid ramp up. Did not cost us time (thanks to accelerator ops who used the time to tune the beam to other halls). <u>https://logbooks.jlab.org/entry/3649136</u>
- DIRC SSP firmware. Caused DAQ rates to drop to 0. Problem promptly patched after intense work by A. Somov and Ben Raydo. <u>https://logbooks.jlab.org/entry/3652894</u>
- TOF RF signal initially reported uncorrelated times. Problem found and fixed by Beni: Main input cable was unplugged with wrong signals coming from an active unlocked phase lock circuit.
- Energy lowered by ~450 MeV due to unsustainable RF-trips (March 5th). Also, the Hall C program requiring highest energy had ended. Lower f.o.m for PrimEx. <u>https://logbooks.jlab.org/entry/3679070</u>
- Short term beam energy drift of up to 10 MeV (CEBAF path length changes, or no energy lock when Hall C was down: Hall A at 1-pass). Overall energy drift during 11.2 GeV period was small (5 MeV). Compare with 12 MeV in Fall 2018. https://logbooks.jlab.org/entry/3679070
- Rapid transmission degradation (days). Not a critical issue with unpolarized beam, but need to be better understood. <u>https://logbooks.jlab.org/entry/3675433</u>
- PS/Main trigger rate time dependence (Not critical for PrimEx thanks to Compton rate normalization) https://logbooks.jlab.org/entry/3675433
- Active collimator signal decay. (Still under investigation. Unclear impact, if any.)

- MCC lost control of Active Collimator. No alarm. Access needed to reboot IOC in Hall D. Need to have alarm and reset buttons in the counting room. https://logbooks.jlab.org/entry/3654003
- Bleedthrough.

- Solenoid power supply motherboard failed. Delayed the solenoid ramp up. Did not cost us time (thanks to accelerator ops who used the time to tune the beam to other halls). <u>https://logbooks.jlab.org/entry/3649136</u>
- DIRC SSP firmware. Caused DAQ rates to drop to 0. Problem promptly patched after intense work by A. Somov and Ben Raydo. <u>https://logbooks.jlab.org/entry/3652894</u>
- TOF RF signal initially reported uncorrelated times. Problem found and fixed by Beni: Main input cable was unplugged with wrong signals coming from an active unlocked phase lock circuit.
- Energy lowered by ~450 MeV due to unsustainable RF-trips (March 5th). Also, the Hall C program requiring highest energy had ended. Lower f.o.m for PrimEx. <u>https://logbooks.jlab.org/entry/3679070</u>
- Short term beam energy drift of up to 10 MeV (CEBAF path length changes, or no energy lock when Hall C was down: Hall A at 1-pass). Overall energy drift during 11.2 GeV period was small (5 MeV). Compare with 12 MeV in Fall 2018. https://logbooks.jlab.org/entry/3679070
- Rapid transmission degradation (days). Not a critical issue with unpolarized beam, but need to be better understood. <u>https://logbooks.jlab.org/entry/3675433</u>
- PS/Main trigger rate time dependence (Not critical for PrimEx thanks to Compton rate normalization)
- Active collimator signal decay. (Still under investigation. Unclear impact, if any.)

- MCC lost control of Active Collimator. No alarm. Access needed to reboot IOC in Hall D. Need to have alarm and reset buttons in the counting room. https://logbooks.jlab.org/entry/3654003
- Bleedthrough.
- Tagger field changed by MCC without notice to Hall D. https://logbooks.jlab.org/entry/3672359 https://logbooks.jlab.org/entry/3672308

- Solenoid power supply motherboard failed. Delayed the solenoid ramp up. Did not cost us time (thanks to accelerator ops who used the time to tune the beam to other halls). <u>https://logbooks.jlab.org/entry/3649136</u>
- DIRC SSP firmware. Caused DAQ rates to drop to 0. Problem promptly patched after intense work by A. Somov and Ben Raydo. <u>https://logbooks.jlab.org/entry/3652894</u>
- TOF RF signal initially reported uncorrelated times. Problem found and fixed by Beni: Main input cable was unplugged with wrong signals coming from an active unlocked phase lock circuit.
- Energy lowered by ~450 MeV due to unsustainable RF-trips (March 5th). Also, the Hall C program requiring highest energy had ended. Lower f.o.m for PrimEx. <u>https://logbooks.jlab.org/entry/3679070</u>
- Short term beam energy drift of up to 10 MeV (CEBAF path length changes, or no energy lock when Hall C was down: Hall A at 1-pass). Overall energy drift during 11.2 GeV period was small (5 MeV). Compare with 12 MeV in Fall 2018. https://logbooks.jlab.org/entry/3679070
- Rapid transmission degradation (days). Not a critical issue with unpolarized beam, but need to be better understood. <u>https://logbooks.jlab.org/entry/3675433</u>
- PS/Main trigger rate time dependence (Not critical for PrimEx thanks to Compton rate normalization)
- Active collimator signal decay. (Still under investigation. Unclear impact, if any.)

- MCC lost control of Active Collimator. No alarm. Access needed to reboot IOC in Hall D. Need to have alarm and reset buttons in the counting room. https://logbooks.jlab.org/entry/3654003
- Bleedthrough.
- Tagger field changed by MCC without notice to Hall D. https://logbooks.jlab.org/entry/3672359 https://logbooks.jlab.org/entry/3672308
- Usual FCal base maintenance, and DAQ, ROC, IOC, Network (slow/unresponsive CSS)... griefs.

Scheduled run time: 1583h (66 days): Feb. 8th-April 15th Acceptable beam used: 875h

 \Rightarrow Running efficiency for overall Spring 2019 period: 55%



Scheduled run time: 1583h (66 days): Feb. 8th-April 15th Acceptable beam used: 875h

 \Rightarrow Running efficiency for overall Spring 2019 period: 55%

DIRC commissioning + CPP

Scheduled run time: 312h (13 days): Feb. $8^{th}-21^{st}$ ABU: 112h (beam available for 139h) \Rightarrow Physics run efficiency: 36% (MCC eff.: 45%)



Scheduled run time: 1583h (66 days): Feb. 8th-April 15th Acceptable beam used: 875h

 \Rightarrow Running efficiency for overall Spring 2019 period: 55%





Scheduled run time: 1583h (66 days): Feb. 8th-April 15th Acceptable beam used: 875h

 \Rightarrow Running efficiency for overall Spring 2019 period: 55%

DIRC commissioning + CPP

Scheduled run time: 312h (13 days): Feb. $8^{\text{th}}-21^{\text{st}}$ ABU: 112h (beam available for 139h) \Rightarrow Physics run efficiency: 36% (MCC eff.: 45%)

PrimEx Overall

Scheduled run time: 1271h (53 days): Feb.8th-Apr.15th ABU: 756h (beam available for 853h) ⇒ Physics run efficiency: 59% (MCC eff.: 67%)



Scheduled run time: 1583h (66 days): Feb. 8th-April 15th Acceptable beam used: 875h

 \Rightarrow Running efficiency for overall Spring 2019 period: 55%

DIRC commissioning + CPP

Scheduled run time: 312h (13 days): Feb. $8^{th}-21^{st}$ ABU: 112h (beam available for 139h) \Rightarrow Physics run efficiency: 36% (MCC eff.: 45%)

PrimEx Overall

Scheduled run time: 1271h (53 days): Feb.8th-Apr.15th ABU: 756h (beam available for 853h) ⇒ Physics run efficiency: 59% (MCC eff.: 67%)

11.6 GeV run

Scheduled run time: 366h (15 days): Feb.8th-Mar.5th ABU: 137h (beam available for 190h) \Rightarrow Physics run efficiency: 37% (MCC eff.: 52%)

11.2 GeV run

Scheduled run time: 366h (15 days): Mar.5th-Apr.15th ABU: 619h (beam available for 663h) \Rightarrow Physics run efficiency: 68% (MCC eff.: 73%)



Scheduled run time: 1583h (66 days): Feb. 8th-April 15th Acceptable beam used: 875h

 \Rightarrow Running efficiency for overall Spring 2019 period: 55%

DIRC commissioning + CPP

Scheduled run time: 312h (13 days): Feb. $8^{th}-21^{st}$ ABU: 112h (beam available for 139h) \Rightarrow Physics run efficiency: 36% (MCC eff.: 45%)

PrimEx Overall

Scheduled run time: 1271h (53 days): Feb.8th-Apr.15th ABU: 756h (beam available for 853h) ⇒ Physics run efficiency: 59% (MCC eff.: 67%)

11.6 GeV run

Scheduled run time: 366h (15 days): Feb.8th-Mar.5th ABU: 137h (beam available for 190h) \Rightarrow Physics run efficiency: 37% (MCC eff.: 52%)

> Effect of not pushing 11.2 GeV run CEBAF energy

Scheduled run time: 366h (15 days): Mar.5th-Apr.15th ABU: 619h (beam available for 663h) \Rightarrow Physics run efficiency: 68% (MCC eff.: 73%)



Scheduled run time: 1583h (66 days): Feb. 8th-April 15th Acceptable beam used: 875h

 \Rightarrow Running efficiency for overall Spring 2019 period: 55%

DIRC commissioning + CPP

Scheduled run time: 312h (13 days): Feb. $8^{th}-21^{st}$ ABU: 112h (beam available for 139h) \Rightarrow Physics run efficiency: 36% (MCC eff.: 45%)

Jefferson Lab Thomas Jefferson National Accelerator Facility Exploring the Nature of Matter

PrimEx Overall

Scheduled run time: 1271h (53 days): Feb.8th-Apr.15th ABU: 756h (beam available for 853h) ⇒ Physics run efficiency: 59% (MCC eff.: 67%)

11.6 GeV run

Scheduled run time: 366h (15 days): Feb.8th-Mar.5th ABU: 137h (beam available for 190h) \Rightarrow Physics run efficiency: 37% (MCC eff.: 52%)

11.2 GeV run

Scheduled run time: 366h (15 days): Mar.5th-Apr.15th ABU: 619h (beam available for 663h)

 \Rightarrow Physics run efficiency: 68% (MCC eff.: 73%)

Not accounting for lower figure of merit

Comparison with other GlueX runs

Spring 2019 Actual Run time: 312h Running efficiency: 36% Production triggers: 0.





Spring 2018 Actual Run time: 1111.8h Running efficiency: 55% Production triggers: 1.5×10¹¹

Spring 2017 Actual Run time: 354.1h Running efficiency: 56% Production triggers:4.7×10¹⁰



Spring 2016 Actual Run time: 458h Running efficiency: 41% Production triggers:6.9×10⁹



Jefferson Lab

Exploring the Nature of Matter

as Jefferson National Accelerator Facility





Fall 2018 Actual Run time: 788h Running efficiency: 52% Production triggers: 8×10¹⁰



Fall 2017 Actual Run time: 10.5h Running efficiency: 3% Production triggers: 0



Fall 2016 Actual Run time: 84h Running efficiency: 5.4% Production triggers: 0



Fall 2015 Actual Run time: 30.2h Running efficiency: 20% Production triggers: 0







Comparison with other GlueX runs

Spring: \$919 +PrimEx Actual Run time: 312h Running efficiency: 36% (55%) Production triggers: 0.



Getting ready...

Spring 2018 Actual Run time: 1111.8h Running efficiency: 55% Production triggers: 1.5×10¹¹

Spring 2017 Actual Run time: 354.1h Running efficiency: 56% Production triggers: 4.7×10¹⁰



<u>Spring 2016</u> Actual Run time: 458h Running efficiency: 41% Production triggers: 6.9×109



Jefferson Lab

Exploring the Nature of Matter

as Jefferson National Accelerator Facility





Fall 2018 Actual Run time: 788h Running efficiency: 52% Production triggers: 8×10¹⁰



Fall 2017 Actual Run time: 10.5h Running efficiency: 3% Production triggers: 0



Fall 2016 Actual Run time: 84h Running efficiency: 5.4% Production triggers: 0



Fall 2015 Actual Run time: 30.2h Running efficiency: 20% Production triggers: 0







Summary of the summary

- Run started nearly on time.
- Good CEBAF performance at 11.6 GeV, then excellent at 11.2 GeV.
- Performance in line with Spring 17-18 and Fall 18 runs.
- Successful DIRC and CPP commissioning.
- Successful first part of PrimEx-η run.
- No significant problems.

Getting ready for high-luminosity GlueX run in Fall.





